

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

1 Identification

Product Name: OEM (GREY)**Other Means of Identification:** Mixture**Recommended Use of the Chemical and Restriction on Use:** OEM (GREY)**Details of Manufacturer or Importer:**

BuddyZ Australia
Suite 120, 7 Clunies Ross court
Eight mile plains QLD 4113

Phone Number: 07 3452 8448**Emergency telephone number:** 0422 122 249**Email:** admin@buddyz.com.au

2 Hazard(s) Identification

Hazardous Nature:

Classified as Hazardous according to the Globally Harmonised System of Classification and Labelling of Chemicals (GHS) and Safe Work Australia criteria.

Not classified as Dangerous Goods according to the Australian Code for the Transport of Dangerous Goods by Road and Rail. (7th edition)

Flammable Liquids 4 H227 Combustible liquid.

Signal Word Warning**Hazard Statements**

H227 Combustible liquid.

Precautionary Statements

P210 Keep away from flames and hot surfaces. No smoking.

P280 Wear protective gloves/protective clothing/eye protection/face protection.

P370+P378 In case of fire: Use to extinguish: CO₂, powder or water spray.

P403+P235 Store in a well-ventilated place. Keep cool.

P501 Dispose of contents/container in accordance with local/regional/national regulations.

3 Composition and Information on Ingredients

Chemical Characterization: Mixtures

Description: Mixture of substances listed below with nonhazardous additions.

Hazardous Components:

CAS: 14464-46-1	Cristobalite	10%
	⚠ Carcinogenicity 1A, H350; STOT RE 1, H372	
CAS: 22984-54-9	2-Butanone, O,O',O''-(methylsilyldiyl)trioxime	6%
	⚠ Acute Toxicity (Oral) 4, H302; Acute Toxicity (Dermal) 4, H312; Acute Toxicity (Inhalation) 4, H332; Skin Corrosion/Irritation 2, H315; Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H335	
CAS: 2224-33-1	2-Butanone, O,O',O''-(ethenylsilyldiyl)trioxime	1.5%
	⚠ Acute Toxicity (Oral) 4, H302; Acute Toxicity (Inhalation) 4, H332; Skin Corrosion/Irritation 2, H315; Serious Eye Damage/Irritation 2A, H319; STOT SE 3, H335	
CAS: 919-30-2	3-aminopropyltriethoxysilane	0.5%
	⚠ Skin Corrosion/Irritation 1B, H314; ⚠ Acute Toxicity (Oral) 4, H302	

Additional information:

The value for cristobalite is the total value, not the respirable fraction.

This product may contain small quantities of respirable cristobalite. Respirable cristobalite is a known carcinogen and can cause serious lung damage. Exposure to this product is not likely to cause harm under

(Contd. on page 2)

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

Product Name: OEM (GREY)

(Contd. of page 1)

normal conditions, but it is recommended to determine the actual exposure through workplace testing.

4 First Aid Measures

Inhalation: If inhaled, remove to fresh air. Seek medical attention if breathing problems develop.

Skin Contact:

In case of skin contact, immediately remove contaminated clothing and wash affected areas with water and soap. Seek medical attention if symptoms occur.

Eye Contact:

In case of eye contact, hold eyelids open and rinse with water for at least 15 minutes. Seek medical attention if symptoms occur.

Ingestion:

If swallowed, do not induce vomiting. Never give anything by mouth to an unconscious person. Seek immediate medical attention.

Symptoms Caused by Exposure: No adverse health effects expected.

5 Fire Fighting Measures

Suitable Extinguishing Media:

Use fire extinguishing methods suitable to surrounding conditions.
Dry chemical or carbon dioxide are recommended.

Specific Hazards Arising from the Chemical:

Hazardous combustion products include oxides of carbon.
Combustible liquid.
Containers close to fire should be removed if safe to do so.

Special Protective Equipment and Precautions for Fire Fighters:

When fighting a major fire wear self-contained breathing apparatus and protective equipment.

6 Accidental Release Measures

Personal Precautions, Protective Equipment and Emergency Procedures:

Wear approved respiratory protection, chemical resistant gloves, protective clothing and safety boots.
Evacuate all non-essential personnel from affected area. Do not breathe vapours. Ensure adequate ventilation. Extinguish all sources of ignition. Avoid sparks and open flames. No smoking.

Environmental Precautions:

In the event of a major spill, prevent spillage from entering drains or water courses.

Methods and Materials for Containment and Cleaning Up:

Stop leak if safe to do so and absorb spill with sand, earth, vermiculite or some other absorbent material.
Collect the spilled material and place into a suitable container for disposal.

7 Handling and Storage

Precautions for Safe Handling:

Use of safe work practices are recommended to avoid eye or skin contact and inhalation of vapours. Use only outdoors or in a well-ventilated area.
Take precautionary measures against static discharge. Food, beverages and tobacco products should not be stored or consumed where this material is in use. Always wash hands before smoking, eating, drinking or using the toilet. Wash contaminated clothing and other protective equipment before storage or re-use. Provide eyewash fountains and safety showers in close proximity to points of potential exposure.

(Contd. on page 3)

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

Product Name: OEM (GREY)

(Contd. of page 2)

Conditions for Safe Storage:

Store in a cool, dry and well ventilated area. Keep container tightly closed when not in use. Protect from heat, sparks, open flames and other sources of ignition. Keep away from strong oxidising agents.

8 Exposure Controls and Personal Protection

Exposure Standards:**CAS: 14464-46-1 Cristobalite**

WES	TWA: 0.1 mg/m ³ respirable dust
-----	---

Engineering Controls: Ensure adequate ventilation of the working area.

Respiratory Protection:

Respiratory protection is not required under normal use conditions.

Use an approved respirator under conditions where exposure to the substance is apparent (e.g. generation of high concentrations of mist or vapour, inadequate ventilation, development of respiratory tract irritation) and engineering controls are not feasible. See Australian Standards AS/NZS 1715 and 1716 for more information.

Skin Protection:

PVC, PVA, nitrile, neoprene, rubber or vinyl gloves. See Australian/New Zealand Standard AS/NZS 2161 for more information. When selecting gloves for use against certain chemicals, the degradation resistance, permeation rate and permeation breakthrough time should be considered.

Occupational protective clothing (depending on conditions in which it has to be used, in particular as regards the period for which it is worn, which shall be determined on the basis of the seriousness of the risk, the frequency of exposure to the risk, the characteristics of the workstation of each worker and the performance of the protective clothing). See Australian/New Zealand Standard AS/NZS 4501 for more information.

Eye and Face Protection:

Eye and face protectors for protection against splashing materials or liquids. See Australian/New Zealand Standard AS/NZS 1337 for more information.

9 Physical and Chemical Properties

Appearance:

Form:	Paste
Colour:	Red
Odour:	No information available
Odour Threshold:	No information available
pH-Value:	Not applicable
Melting point/freezing point:	No information available
Initial Boiling Point/Boiling Range:	No information available
Flash Point:	65 °C (Closed Cup)
Flammability:	Combustible
Auto-ignition Temperature:	No information available
Decomposition Temperature:	No information available
Explosion Limits:	
Lower:	No information available
Upper:	No information available
Vapour Pressure:	No information available
Relative Density:	No information available
Vapour Density:	No information available
Evaporation Rate:	No information available
Solubility in Water:	Not soluble in water.
Partition Coefficient (n-octanol/water):	No information available

(Contd. on page 4)

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

Product Name: OEM (GREY)

(Contd. of page 3)

Viscosity: No information available

10 Stability and Reactivity

Possibility of Hazardous Reactions: Hazardous polymerisation will not occur.**Chemical Stability:** Stable at ambient temperature and under normal conditions of use.**Conditions to Avoid:** Heat, sparks, open flames and other sources of ignition.**Incompatible Materials:** Strong oxidising agents.**Hazardous Decomposition Products:** Oxides of carbon.

11 Toxicological Information

Toxicity:**LD₅₀/LC₅₀ Values Relevant for Classification:****CAS: 14464-46-1 Cristobalite**Oral LD₅₀ >5,000 mg/kg (rat)Inhalation LC₅₀/4 h >2.6 mg/l (rat)**CAS: 919-30-2 3-aminopropyltriethoxysilane**Oral LD₅₀ 1,780 mg/kg (rat)Dermal LD₅₀ 4,000 mg/kg (rabbit)**Acute Health Effects****Inhalation:** No adverse health effects expected.**Skin:** No adverse health effects expected.**Eye:** No adverse health effects expected.**Ingestion:** No adverse health effects expected.**Skin Corrosion / Irritation:** Based on classification principles, the classification criteria are not met.**Serious Eye Damage / Irritation:** Based on classification principles, the classification criteria are not met.**Respiratory or Skin Sensitisation:** Based on classification principles, the classification criteria are not met.**Germ Cell Mutagenicity:** Based on classification principles, the classification criteria are not met.**Carcinogenicity:**

Silica dust, crystalline, in the form of quartz or cristobalite is classified by IARC as Group 1 - Carcinogenic to humans.

Reproductive Toxicity: Based on classification principles, the classification criteria are not met.**Specific Target Organ Toxicity (STOT) - Single Exposure:**

Based on classification principles, the classification criteria are not met.

Specific Target Organ Toxicity (STOT) - Repeated Exposure:

Causes damage to organs through prolonged or repeated exposure.

Aspiration Hazard: Based on classification principles, the classification criteria are not met.**Chronic Health Effects:** No information available**Existing Conditions Aggravated by Exposure:** No information available**Additional toxicological information:** No information available

(Contd. on page 5)

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

Product Name: OEM (GREY)

(Contd. of page 4)

12 Ecological Information

Ecotoxicity:

Aquatic toxicity:

CAS: 14464-46-1 Cristobalite

EC₅₀/48 h >100 mg/l (daphnia)LC₅₀/96 h >100 mg/l (brachydanio rerio)

CAS: 919-30-2 3-aminopropyltriethoxysilane

EC₅₀/48 h 331 mg/l (daphnia)LC₅₀/96 h 934 mg/l (brachydanio rerio)

Persistence and Degradability: No further relevant information available.

Bioaccumulative Potential: No further relevant information available.

Mobility in Soil: No further relevant information available.

Other adverse effects: No further relevant information available.

13 Disposal Considerations

Disposal Methods and Containers: Dispose according to applicable local and state government regulations.

Special Precautions for Landfill or Incineration:

Please consult your state Land Waste Management Authority for more information.

14 Transport Information

UN Number Not regulated

Proper Shipping Name Not regulated

Dangerous Goods Class Not regulated

Packing Group: Not regulated

15 Regulatory Information

Australian Inventory of Chemical Substances:

CAS: 9016-00-6 Poly[oxy(dimethylsilylene)]

CAS: 9006-65-9 Dimethicone

CAS: 14464-46-1 Cristobalite

CAS: 22984-54-9 2-Butanone, O,O',O''-(methylsilyldiene)trioxime

CAS: 2224-33-1 2-Butanone, O,O',O''-(ethenylsilyldiene)trioxime

CAS: 919-30-2 3-aminopropyltriethoxysilane

Standard for the Uniform Scheduling of Drugs and Poisons (SUSMP) - Poison Schedule:

Not Scheduled.

16 Other Information

Date of Preparation or Last Revision: 17.09.2018

Prepared by: MSDS.COM.AU Pty Ltd

www.msds.com.au

Abbreviations and acronyms:

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

CAS: Chemical Abstracts Service (division of the American Chemical Society)

(Contd. on page 6)

Safety Data Sheet

according to WHS Regulations

Printing date 17.09.2018

Revision: 17.09.2018

Product Name: OEM (GREY)

(Contd. of page 5)

LC₅₀: Lethal concentration, 50 percentLD₅₀: Lethal dose, 50 percent

IARC: International Agency for Research on Cancer

STEL: Short Term Exposure Limit

TWA: Time Weighted Average

NES: National Exposure Standard (Safe Work Australia - Workplace Exposure Standards For Airborne Contaminants)

Flammable Liquids 4: Flammable liquids – Category 4

Acute Toxicity (Oral) 4: Acute toxicity – Category 4

Skin Corrosion/Irritation 1B: Skin corrosion/irritation – Category 1B

Skin Corrosion/Irritation 2: Skin corrosion/irritation – Category 2

Serious Eye Damage/Irritation 2A: Serious eye damage/eye irritation – Category 2A

Carcinogenicity 1A: Carcinogenicity – Category 1A

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3

STOT RE 1: Specific target organ toxicity (repeated exposure) – Category 1

Disclaimer

This SDS is prepared in accord with the Safe Work Australia document “Code of Practice for the Preparation of Safety Data Sheets for Hazardous Chemicals - February 2016”

The information contained in this safety data sheet is provided in good faith and is believed to be accurate at the date of issuance. Buddyz makes no representation of the accuracy or comprehensiveness of the information and to the full extent allowed by law excludes all liability for any loss or damage related to the supply or use of the information in this material safety data sheet. MSDS.COM.AU Pty Ltd is not in a position to warrant the accuracy of the data herein. The user is cautioned to make their own determinations as to the suitability of the information provided to the particular circumstances in which the product is used.